

# MoS2

## ANTI WEAR TREATMENT GEAR BOX / PS / AXELS

VERSION 1 - JANUARY 2020

WWW.MECATECH-PERFORMANCES.COM

TECHNICAL DATA

### DEFINITION

- ◆ Colloidal molybdenum disulphide anti-wear treatment.
- ◆ Reduces noises and lowers frictions while forming a high resistance lubricating film on all sliding surfaces.
- ◆ Reduces wear and stops the phenomena of gears wear. Facilitates gear shifting.
- ◆ Recommended in case of strong wear, running noises, and harsh use.

### OPERATING INSTRUCTIONS

- ◆ Dosage from 3 to 5 % :  
A 100mL-bottle for 2 or 3 litres of oil.
- ◆ Shake well before use, then introduce the dose needed in the crankcase using a clean syringe.
- ◆ Recommended for transmissions, transfer boxes and differentials.
- ◆ Not for use in automatic transmissions and limited slip differentials.
- ◆ Compatible with all kinds of mineral or synthetic oils.
- ◆ Recommended in addition to GDA® evolution Ref. MT025 in case of noisy top gears or axels.

### PHYSICOCHEMICAL CHARACTERISTICS

- |                          |                |
|--------------------------|----------------|
| ◆ <b>Colour</b>          | amber          |
| ◆ <b>Odour</b>           | characteristic |
| ◆ <b>Density at 20°C</b> | 0.955          |



## SAFETY DATA

- ◆ Consult the SDS of the products available on our website [www.mecatech-performances.com](http://www.mecatech-performances.com).

## PACKAGING

- ◆ Packaging : 100mL-dose
- ◆ Reference : MT022

*The content of this technical sheet is aimed at giving you advices. It does not imply any commitment on our part.*