

SILICONE HV

Release agent, clean lubrication, polish

VERSION 1 - JANUARY 2020

WWW.MECATECH-PERFORMANCES.COM

TECHNICAL DATA

DEFINITION

- ◆ Release agent for plastic and rubber molds. Lubrication for mechanisms in textile industry, paper industry, leather industry...
- ◆ Lubrication of precision instruments, in micromechanics, laboratory, watchmaking and meters...
- ◆ Domestic lubrication of weapons, sewing machines, rails, drawers...
- ◆ Cleaner for skais, dashboards, waterproofing of ignition leads, spark plugs, coils, textiles, leathers...

INTRODUCTION

- ◆ Colourless and odourless after the solvents evaporate
- ◆ Resists to temperature and to oxidation
- ◆ Water-repellent
- ◆ Leaves no stain
- ◆ Its 360° valve allows a use in all positions

OPERATING INSTRUCTIONS

- ◆ Shake well before use.
- ◆ The molds and other surfaces to be treated should be first degreased using usuals solvents.
- ◆ Spray on the surfaces, wait for 2-3 minutes and repeat if necessary.



PHYSICOCHEMICAL CHARACTERISTICS:

- | | |
|-----------------------------|-----------------------|
| ◆ Aspect | Clear |
| ◆ Colour | Colourless |
| ◆ Odour | Light |
| ◆ Density at 15°C NFT 60101 | 690 kg/m ³ |
| ◆ Flash point VC ASTMD 56 | <0°C |

SAFETY DATA :

- ◆ Consult the SDS of the products available on our website www.mecatech-performances.com. Professional use.

PACKAGING

- ◆ Packaging : 650 / 400 ml spray can
- ◆ Reference : 455012

*The content of this technical sheet is aimed at giving you advices.
It does not imply any commitment on our part.*